

3M0-250 3Com Certification

3COM 3Com Certified Enterprise LAN Post-Sales Expert version 1.0


Practice Exam: 3M0-250 Exams

Exam Number/Code: 3M0-250

Exam Name: 3Com Certified Enterprise LAN Post-Sales Expert version 1.0

Questions and Answers: 99 Q&As

([3Com Certification](#))



Exam : [3M0-250](#)

"3Com Certified Enterprise LAN Post-Sales Expert version 1.0", also known as 3M0-250 exam, is a 3COM certification. With the complete collection of questions and answers, TestInside has assembled to take you through 99 Q&As to your 3M0-250 Exam preparation. In the 3M0-250 exam resources, you will cover every field and category in 3COM Certification helping to ready you for your successful 3COM Certification.

Quality and Value for the 3M0-250 Exam TestInside Practice Exams for 3COM **3Com Certification** Certification 3M0-250 are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development.

TestInside provide the professional Q&A.

1. We offer free update service for three month.

After you purchase our product, we will offer free update in time for three month.

2. High quality and Value for the 3M0-250 Exam.

3M0-250 simulation test questions, including the examination question and the answer, complete by our senior IT lecturers and the 3Com Certification product experts, included the current newest 3M0-250 examination questions.

3. 100% Guarantee to Pass Your 3Com Certification exam and get your 3Com Certification Certification.

If you do not pass the 3COM Certification 3M0-250 exam (3Com Certified Enterprise LAN Post-Sales Expert version 1.0) on your first attempt using our TestInside testing engine and pdf file, we will give you a FULL REFUND of your purchasing fee.

use TestInside 3M0-250 Q&A ensure you pass the exam at your first try.

TestInside professional provide 3Com Certification 3M0-250 the newest Q&A, completely covers 3M0-250 test original topic. With our complete 3Com Certification resources, you will minimize your 3Com Certification cost and be ready to pass your 3M0-250 tests on Your First Try, 100% Money Back Guarantee included!

[3COM 3M0-250](#) Test belongs to one of the 3Com Certification certified test, if needs to obtain the 3Com Certification certificate, you also need to participate in other related test, the details you may visit the [3Com Certification](#) certified topic, in there, you will see all related 3Com Certification certified subject of examination.

TestInside Testing Engine Features

Comprehensive questions and answers about 3M0-250 exam

3M0-250 exam questions accompanied by exhibits

Verified Answers Researched by Industry Experts and almost 100% correct

3M0-250 exam questions updated on regular basis

Same type as the certification exams, 3M0-250 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 3M0-250 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : 3COM 3M0-250

Title : 3Com Certified Enterprise LAN Post-Sales Expert version 1.0

1. GARP VLAN Registration Protocol (GVRP) maintains and distributes Virtual LAN (VLAN) registration information only about the dynamically created VLANs using GARP.

- A. True
- B. False

Answer: B

2. You have already configured and enabled individual switch ports for IEEE 802.1X Network Login. What is required for authentication to be activated on the ports?

- A. From the System View, enable 802.1X Network Login
- B. From the Ethernet Port View, set the port access control mode
- C. From the System View, configure the authentication method for 802.1X users
- D. From the Ethernet Port View, configure the authentication method, i.e., chap, pap, eap, etc.

Answer: A

3. Which best defines the mechanism of IEEE 802.1X Network Login?

- A. An authenticator requests access to network services; the authentication server enforces authentication before allowing access to the network and validates the supplicant on behalf of the authenticator
- B. A supplicant requests access to network services; the authenticator enforces authentication before allowing access to the network; the authentication server validates the supplicant on behalf of the authenticator
- C. A supplicant requests access to network services; the authentication server enforces authentication before allowing access to the network; the authenticator validates the supplicant on behalf of the authentication server

Answer: B

4. Which three are Switch 5500 configuration requirements when creating an eXpandable Resilient Networking (XRN) Fabric? (Choose three.)

- A. All units in the stack must have the same sysname
- B. All units in the stack must be running the same software version
- C. A mixture of switch models can be used to create a single XRN Fabric
- D. Switch 5500-SI/EI up/down ports must be enabled for fabric mode
- E. A switch must be initialized after it has been added to an existing XRN Fabric

Answer: ABD

5. An IP address must be configured on a switch before it can be managed using Telnet.

- A. True
- B. False

Answer: A

6. Which Switch 5500 PWR LED condition indicates the switch is powered-up and operating normally?

- A. Off
- B. Green
- C. Green flashing
- D. Solid green when not transmitting user data and flashing green when transmitting user data

Answer: B

7. Click on the exhibit button.

Which Switch 7700 command shows all the hardware and software information on the modules (review the output shown in the exhibit)?

- A.[SW7700] display device
- B.[SW7700] display version
- C.[SW7700] display interfaces
- D.[SW7700] display current-configuration

Answer: B

8. Which Switch 5500 model(s) does not support Distributed Resilient Routing (DRR)?

- A.Switch 5500-EI
- B.Switch 5500-SI
- C.Switch 5500G-EI
- D.All of the above

Answer: B

9. What is the reason to connect the up port on the bottom Switch 5500 in the stack to the down port of the top Switch 5500 in the same stack?

- A.Reliability - creates a resilient topology
- B.Security - prevents an unauthorized user from connecting to the switch stack
- C.Performance - creates the 48-Gbps eXpandable Resilient Networking (XRN) Fabric
- D.Management - enables Distributed Resilient Routing (DRR) on the Switch 5500-SI

Answer: A

10. How does the network administrator configure the up/down Switch 5500-EI/SI ports to operate in fabric mode?

- A.By default, the up/down ports are enabled for fabric mode
- B.Execute the command `xm-fabric authentication-mode simple`
- C.Execute the command `resilient-arp enable x/x/x` where x/x/x identifies the unit and port number
- D.Execute the command `fabric-port gigabit x/x/x enable` where x/x/x identifies the unit and port number

Answer: D

11. What is the effect of the Simple Network Management Protocol (SNMP) switch command `snmp-agent target-host trap address udp-domain 129.102.149.23 udp-port 5000 params securityname 3comprivate`?

- A.Configures the switch with a default community string name of 3comprivate
- B.Enables the SNMP trap functions on a switch with IP address 129.102.149.23
- C.Configures the switch SNMP agent to send traps to the network management station at IP address 129.102.149.23
- D.Enables the SNMP trap functions and sets the default community string name of 3compublc on a switch with IP address 129.102.149.23

Answer: C

12. How would you view the configuration information that is running on a switch?

- A.Use the `display startup` command
- B.Use the `display version` command
- C.Use the `display saved-configuration` command
- D.Use the `display current-configuration` command

Answer: D

13. Which security standard is defined by IEEE 802.1X Network Login?

- A.Encryption standard for network authorization
- B.Port-based Network Access Control protocol standard
- C.Extensible Authentication Protocol (EAP) standard for network authorization

D.Authentication, Authorization and Accounting (AAA) standard for network access

Answer: B

14. Which two are functions of Extensible Authentication Protocol (EAP)? (Choose two.)

A.Provides a framework and transport for the exchange of authentication information between the authenticator and the supplicant

B.Provides encapsulation for the exchange of information between the authenticator and authentication server

C.Provides the mechanism for locking/unlocking a switch port based on the results of the supplicants authentication

D.Provides the mechanism for defining what network resources a user may access based on the authentication information

Answer: AB

15. You have configured multiple OSPF areas on your network. How do the different OSPF areas communicate with each other?

A.The Designated Router (DR) uses multicast routing to broadcast advertisements to the other area DRs

B.The Designated Router (DR) connects each OSPF area to the main backbone network and communicates with the other areas

C.The Area Border Router (ABR) connects each OSPF area to the main backbone network and communicates with the other areas

D.The Autonomous System Border Router (ASBR) connects each OSPF area to the main backbone network and communicates with the other areas

Answer: C

16. Which switch command shows what is installed in the switch and the current operational status?

A.[SW8800-14slot] display device

B.[SW8800-14slot] display system

C.[SW8800-14slot] display startup

D.[SW8800-14slot] display current-configuration

Answer: A

17. You have issued the switch debugging command debugging rip packets from the management terminal, but you are not receiving any debug output. What is the reason you are not getting any debug output from the switch?

A.RIP has not been enabled, and therefore there is no debug output

B.Output from the debugging command only goes to the syslog server

C.You forgot to issue the enable debugging command at the System View

D.You forgot to issue the terminal debugging command, directing the output to your management terminal

Answer: D

18. Which two are general Link Aggregation (LA) configuration rules that must be followed when creating an LA group? (Choose two.)

A.A member link port can only belong to one LA group

B.Aggregated links are mutually exclusive with roving analysis and mirror ports

C.A port must be configured for resilient links before it can be configured as a member of an LA group

D.LA ports can only be configured if Link Aggregation Control Protocol (LACP) is enabled on the switches

Answer: AB

19. What is the result of the command boot boot-loader file-url?

A.Reboots the switch using the file-url for the operational code

B.Updates the switch BootROM with the file-url on the system flash

C.Reboots the switch fabric only using the file-url for the operational code

D.Specifies the switch to use file-url for the operational code on the next boot

Answer: D

20. How must the MAC Radius Authenticated Device Access (RADA) address be configured on the Switch 5500?

- A.Hexadecimal IP address only
- B.Hexadecimal MAC address only
- C.Binary or hexadecimal IP or MAC address
- D.Binary, decimal or hexadecimal MAC address

Answer: B

[More 3M0-250 Information](#)

Related 3M0-250 Exams

[3M0-331](#) 3Com WAN Specialist Final Exam v2.0

[3M0-300](#) 3Com WAN Expert Final Exam v2.4

[3M0-701](#) 3Com Certified IP Telephony NBX Expert Final Exam V3.0

[3M0-250](#) 3Com Certified Enterprise LAN Post-Sales Expert version 1.0

[3M0-211](#) Certified Enterprise LAN Specialist

[3M0-600](#) Wireless Specialist Final Exam

[3M0-212](#) Certified Enterprise LAN Pre-Sales Expert version 3.2

[3M0-700](#) Certified IP Telephony Specialist

[3M0-200](#) 3COM 3M0-200

Other 3COM Exams

[3M0-300](#) [3M0-211](#) [3M0-212](#) [3M0-600](#) [3M0-331](#) [3M0-200](#) [3M0-250](#) [3M0-701](#)

[3M0-700](#)