



4A0-106 exam questions updated on regular basis

Same type as the certification exams, 4A0-106 exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 4A0-106 exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo do not include the question's picture.

Exam : Alcatel Lucent 4A0-106

Title : Alcatel-Lucent Virtual Private Routed Networks

1. Which of the following statements are true regarding P devices in an MPLS VPRN? (Choose two.)

- A. Participate in service provider core routing
- B. P devices are not required to be MPLS enabled. MPLS is only required on the PE devices
- C. Run a common routing protocol with the CE router
- D. Must support MP-BGP
- E. Do not have any connections to the CE
- F. Must be aware of the VPRNs

Answer: AE

2. Which of the following devices would typically have VRF instances?

- A. Any CE device
- B. Any PE device
- C. Any P device
- D. Any router in the service provider core
- E. Any customer router

Answer: B

3. Complete the following statement. In a VPRN, the label signaled by RSVP-TE is used to \_\_\_\_\_.

- A. Identify the egress PE in the MPLS domain
- B. Signal the egress VPRN ID
- C. Identify the ingress PE in the MPLS domain
- D. transport route updates between PEs

Answer: A

4. Which of the following terms also correctly describes a Layer 3 VPN? (Choose three)

- A. VPRN
- B. BGP/MPLS VPN
- C. VLL
- D. VPLS
- E. IP-VPN
- F. ePipe

Answer: ABE

5. Complete the following statement. In a VPRN, the label signaled by RSVP-TE is used to \_\_\_\_\_.

- A. Identify the egress PE in the MPLS domain
- B. Signal the egress VPRN ID
- C. Identify the ingress PE in the MPLS domain
- D. transport route updates between PEs

Answer: A

6. Complete the following statement. In a VPRN, the inner label is used to \_\_\_\_\_.

- A. Identify the customer network on the egress PE

- B. Establish the LSPs between PE devices
- C. Identify the egress PE in the MPLS domain
- D. Identify the customer network on the ingress PE

Answer: A

7. What are the main functions of a Layer 3 VPN? (Choose three).

- A. Distributing customer routing information between sites
- B. Forwarding customer data packets
- C. Providing an integrated billing solution
- D. Maintaining separation between distinct customer networks
- E. Allowing the implementation of Layer 3 devices in the provider core

Answer: ABD

8. Choose the answer that best completes the following sentence. The CE device is typically configured with \_\_\_\_\_.

- A. A single routing protocol for exchanging routes with both the internal customer routers and with the PE
- B. MP-BGP to exchange routes with the PE.
- C. MPLS and a routing protocol for the exchange of labels and routes with the PE
- D. MPLS for exchanging labels with other CE devices
- E. A routing protocol for exchanging routes with the internal customer routers and a routing protocol for exchanging routes with the PE

Answer: E

9. Which of the following statements is true? Choose the best answer.

- A. A P router may forward customer packets to their destination without the presence of a route to that destination
- B. The ingress PE router may forward customer packets to their destination without the presence of a route to that destination
- C. The egress PE router may forward customer packets to their destination without the presence of a route to that destination
- D. Any provider core router (P or PE) may forward customer packets to their destination without the presence of a route to that destination

Answer: A

10. What operation is performed by a P device on the label signaled by MP-BGP when it receives a labeled packet for a VPRN service?

- A. It will label switch the packet based on this label
- B. It will decrement the TTL and label switch the packet based on this label
- C. It will SWAP the label for a new label and then label switch the packet
- D. The P router does not perform any operation on this label

Answer: D

11. Which protocol is used to exchange customer VPRN routes between PE devices?

- A. OSPF
- B. ISIS
- C. MP-BGP
- D. BGP
- E. Targeted LDP

Answer: C

12. What are the two primary problems the service provider must consider when providing traditional Layer 3 VPN services using only a single common routing table in the provider core? (Choose two)

- A. Memory exhaustion in the provider core
- B. Route leaking between the customer networks

- C. CPU utilization for route processing
- D. Unwanted packet forwarding between customer networks

Answer: BD

13. When a Service Provider offers VPRN services to its customers, which of the following functions are expected to be the responsibility of the Service Provider? (Choose three)

- A. Distributing the customer generated labels between sites
- B. Distributing the customer routing information between sites
- C. Forwarding the customer originated data packets to the appropriate destination
- D. Forwarding the provider originated data packets to the appropriate customer site
- E. Providing secure layer 3 routing exchange between sites

Answer: BCE

14. In a traditional layer 3 VPN which of the following will be an issue when there is overlapping address space between two customers? Choose the best answer.

- A. There will be increased memory usage on the PE
- B. There will be increased CPU utilization on the PE
- C. The CE will reject the overlapping prefix
- D. The PE will not recognize the prefixes as being different
- E. There is no issue with overlapping address space in a traditional Layer 3 VPN

Answer: D

15. In a VPRN the PE device is configured to run which of the following protocols? (Choose three.)

- A. MP-BGP for exchanging customer routes with other PEs
- B. A routing protocol for exchanging customer routes with the CE
- C. MPLS for exchanging labels with other provider core devices
- D. MPLS for exchanging labels with the CE devices
- E. Targeted LDP for exchanging VPRN labels with other PE devices
- F. A label signaling protocol for defining transport tunnels between PE and CE devices

Answer: ABC

### [More 4A0-106 Information](#)

#### **Related 4A0-106 Exams**

[4A0-100](#) Alcatel-Lucent Scalable IP Networks

[4A0-101](#) Alcatel-Lucent Interior Routing Protocols and High Availability

[4A0-103](#) Alcatel-Lucent Multiprotocol Label Switching

[4A0-106](#) Alcatel-Lucent Virtual Private Routed Networks

[4A0-109](#) Alcatel-Lucent Triple Play Services

[4A0-104](#) Alcatel-Lucent Services Architecture

[087-301](#) LCIE VoIP THEORY, STANDARDS AND PROTOCOLS EXAM DTT301T

[087-370](#) LCIE DSL Associate Certification Exam DTT370T

[087-070](#) LCIE Multi-Service WAN Certification Exam DTT070T

[4A0-107](#) Alcatel-Lucent Quality of Service

[4A0-105](#) Alcatel-Lucent Virtual Private LAN Services

[4A0-110](#) Alcatel-Lucent Advanced Troubleshooting

[086-470](#) LCIE Metro Optical Associate Beta Exam DTT470T

[087-170](#) LCIE Remote Access Certification Exam DTT170T

4A0-108 Alcatel-Lucent Multicast Protocols

4A0-102 Alcatel-Lucent Border Gateway Protocol

**Other Alcatel Lucent Exams**

<u>4A0-101</u>	<u>4A0-105</u>	<u>4A0-108</u>	<u>4A0-109</u>	<u>4A0-103</u>	<u>087-370</u>	<u>4A0-110</u>	<u>086-470</u>
<u>087-301</u>	<u>4A0-107</u>	<u>087-170</u>	<u>4A0-100</u>	<u>4A0-106</u>	<u>4A0-104</u>	<u>4A0-102</u>	<u>087-070</u>